Material Safety Data Sheet

Date:	March 12, 2015	March 12, 2015		
Product:	Antiseptic Iodine Spray / Iospray (1%)			
Product Information:	Iodine Spray			
Product Code: :	10L-ISPRA			
D.I.N.	0049600			
Manufacturer/Supplier:	Dominion Veterinary labs LTD. 1199 Sanford St Winnipeg , Manitoba R3E 3A1 Telephone: (204)-586-3484 Fax: (204)-943-9612			
Product use: As an aid in the tabrasions, navel stumps, docking injections or surgical procedure	gs, and castration wounds.			
Chemical Identity:	Blend			
CAS No. and name:	Blend	Blend		
Formula and M.Wt.:	Blend			
WHMIS classification:	Flammable liquid, Class B-2 Toxic Material, Class D-2B			
TDG classification:	Flammable Liquid, n.o.s. (Isopropyl Alcohol) Class: 3 UN 1993 Packing Group: II Exemption: Limited Quantity 1.17			
Hazardous Ingredients				
Chemical Identity	CAS#/NA#/UN#	Conc.(w/w)	LD50	
Isopropanol	67-63-0	60-100%	LD50(Oral Rat) 5045 mg/kg	
PVP- Polyvinylpyrrolidone	25655-41-8	100%	LD50(Oral Rat)5900 mg/kg	

Physical Data				
Physical State:	Liquid			
Appearance and Odou	r: Dark brown liquid:	aromatic odour		
Odour threshold:	40 ppm - Isopropanol	Boiling Pt. (Deg.C):	 N/A	
Specific Gravity:	90	Freezing Pt.(Deg.C):	 N/A	
Vapour Pressure:	N/A	рН: 3.5		
Vapour Density:	N/A	Density(g/mL):.90/ml		
Evapouration Rate:	N/A	Water Solubility: Soluble		
	Fire or Ex	plosion Hazards		
Means of extinction: Large fires-Us	se water spray, foam, dry chemi	cal, or carbon monoxide.		
Small fires-(Sa	ame as above)			
Flashpoint and method	d of determination:(TCC, Deg	. C)-19 C - Pensky-Martens		
Upper flammable limi	t: N/A			
Lower flammable limi	t: N/A			
Auto-Ignition Temper	ature: N/A			
Hazardous combustion	n products: Carbon oxides and	products of incomplete combustion.		
Explosion Data- Sensi	tivity to mechanical impact: 1	Not sensitive		

MSDS Antiseptic Iodine Spray (1%) Page 2 of 5

Explosion Data-Sensitivity to static discharge: Potential for fire and/or explosion. Grounding and use of explosion-proof equipment is required.

Reactivity Data Chemical Stability: Stable under normal conditions. Hazardous polymerization will not occur. Incompatable Substances: Avoid strong oxidizing and reducing agents. Conditions of reactivity: Avoid contamination with reactive substances. Avoid excessive heat. Avoid heating above flashpoint. Hazardous decomposition products: Acrid smoke and fumes emitted when heated to decomposition. Oxides of carbon. **Toxilogical properties Effects of Accute Exposure: Route of Entry: Skin contact:** Contact may cause irritation, redness, swelling, or dermatitis. Will cause painful burning or stinging of eyes and lids, watering Eye absorption: of eyes, and inflammation of conjunctiva. **Inhalation:** Vapours could cause headache, nausea, dizziness, and respiratory irritation if inhaled. **Ingestion:** May cause abdominal discomfort, nausea, vomiting, and diarrhea. Doses of 150 mL and above can be fatal. Effects of chronic exposure: Skin irritation or dermatitis may occur upon frequent or prolonged contact. **Exposure limits:** TLV= 400 ppm-Isopropanol (ACGIH) **Irritancy of product:**

Eye:Severe irritant

Skin:Moderate irritant

Sensitization to material: No evidence to indicate sensitizer.

Carcinogenicity: Product has not been listed as a carcinogen or potential carcinogen by either the ACGIH or the IARC.

Reproductive toxicity: N/A

Teratogenicity: N/A

Mutagenicity: N/A

Toxicologically synergistic products: N/A

Preventive Measures

Personal protective equipment: Chemical goggles, impervious gloves and protective clothing as required to prevent contact. Use NIOSH-approved air-purifying respirator with chemical cartridge for protection against organic vapours.

Engineering controls: General ventillation with a good source of make-up air recommended for all indoor situations. Local ventillation recommended at source of contaminant generation. Ventillation should be adequate enough to maintain air concentrations below the designated exposure limit.

Handling procedures and equipment: Avoid prolonged or frequent contact when handling material. Avoid breathing mist or vapour. Use a NIOSH-approved chemical-cartridge respirator, if adequate ventillation cannot be provided. Avoid skin or eye contact. Protective measures during repair/maintainance of equipment: Wash equipment thouroughly with steam or warm water until clean. Check for flammables with an explosion meter and also check the oxygen level with an oxygen meter. In all cases, follow good industrial safety practices before entering equipment.

Storage requirements: Keep container closed when not in use. Store in cool and dry location away from oxidizing and reducing agents.

Special shipping information: Handle according to the requirements set out in the Transport of Dangerous Goods regulations for: For bulk shipments only: ISOPROPANOL SOLUTION, UN#1219, CLASS 3, P.G. II

Procedures for handling leaks or spills: Eliminate sources of ignition. Collect into waste container. Absorb remaining product with earth or sand and dispose of with solid waste. Wash spill site after material pick-up. Do not breathe vapours. Use NIOSH- approved respirator if exposed to vapours. Avoid drainage of spilled material to sewers or waterways.

Waste disposal: Dispose of waste according to fed be used directly as a fuel stock with appropriate en directly with or without other flammable solvent ac	missions control equipment. Otherwise, incinerate
Firs	st Aid Measures
Skin contact: Immediately flush skin with plenty of clothing and shoes. Call a physician. Wash clothes	
Eye contact: Immediately flush eyes with water for lenses should not be worn when working with this r	± •
Inhalation: Remove to fresh air. If not breathing, to-mouth. If breathing is difficult, give oxygen. Ca	· · · · · · · · · · · · · · · · · · ·
Ingestion: Induce vomitting by giving two glasses give anything by mouth to an unconcious person. C	
	Prepared by: David Earn
	Date: March 12, 2015
	Checked By:D.Earn

The information contained herein is, to the best of our knowledge, true and accurate. Any recommendations or suggestions are made without obligation on our part and the Company accepts no liability to any customers, their employees or any other person whatsoever for any loss, injury or damage whether direct or consequential, which may be caused by an error or emission from this sheet even if negligence or otherwise.