# **Safety Data Sheet**



1.800.982.2017 | shapleys.com

Issue Date 01-Aug-2013 Revision Date: 25-Sep-2013 Version 1

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

SDS # 60011-EU Product Code STU-DB

Product Name Show Touch Up-Dark Brown

Formula 60011

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use Cover stains and blemishes

1.3. Details of the Supplier of the Safety Data Sheet

# **Supplier**

Shapley's 11650 Chitwood Dr. Fort Myers, FL 33908 www.shapleys.com

For further information, please contact

Contact Point Phone: 239-415-2275

Fax: 239-415-2277

Email Address info@shapleys.com

1.4. Emergency telephone number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

# **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the Substance or Mixture

# Regulation (EC) No 1272/2008

Aspiration toxicity	Category 1
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Chronic aquatic toxicity	Category 2
Flammable Aerosols	Category 1

# Classification according to 67/548/EEC

Full text of R-phrases: see section 16

# **Hazard Symbols**

F+ - Extremely flammable

Xn - Harmful

N - Dangerous for the environment

### R-code(s)

F+;R12 - Repr. cat. 3;R62 - Xn;R48/20 - Xn;R65 - Xi;R38 - R67 - N;R51/53

## 2.2. Label Elements



# Signal Word

Danger

# **Hazard Statements**

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H340 - May cause genetic defects

H350 - May cause cancer

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H222 - Extremely flammable aerosol

60011-EU - Show Touch Up-Dark Brown

# Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use

P281 - Use personal protective equipment as required

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### 2.3. Other Hazards

### **General Hazards**

None known

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Hexane	Present	110-54-3	57-63	F; R11 Xi; R38 N; R51-53 Repr.Cat.3; R62 Xn; R65-48/20 R67	Skin Irrit. 2 (H315) Repr. 2 (H361f) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225) Skin Irrit. 2 (H315) Flam. Liq. 2 (H225) Repr. 2 (H361) STOT RE 2 (inhalation) STOT SE 3 () Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411)	Not determined
Petroleum gases, liquified, sweetened	Present	68476-86-8	27-33	f+; R12	Muta. 1B (H340) Carc. 1B (H350) Flam. Gas 1 (H220) Press. Gas	Not determined
Stoddard solvent	Present	8052-41-3	1-5	Xn; R65	Muta. 1B (H340) Carc. 1B (H350) Asp. Tox. 1 (H304)	Not determined
Propylene glycol monomethyl ether acetate	Present	108-65-6	1-5	R10	Flam. Liq. 3 (H226) Flam. Liq. 3 (H226)	Not determined
Iron(III) oxide	Present	1309-37-1	1-5	-	Not determined	Not determined

# Full text of R-phrases: see section 16

# Full text of H- and EUH-phrases: see section 16

### **Additional Information**

Substances without a classification are included because they have established occupational exposure limits

# **SECTION 4: FIRST AID MEASURES**

## 4.1. Description of First Aid Measures

General Advice If exposed or concerned: Get medical advice/attention.

Eye Contact If adverse effects occur, rinse eyes with large amounts of water until irritation subsides. If

eve irritation persists: Get medical advice/attention.

**Skin Contact**Wash with soap and water. Apply hand cream. Get medical attention if irritation occurs.

Take off contaminated clothing. Wash contaminated clothing before reuse.

**Inhalation** Remove to fresh air.

**Ingestion** Do not induce vomiting. Call a physician or poison control center immediately.

## 4.2. Most Important Symptoms and Effects, Both Acute and Delayed

**Symptoms** Aspiration hazard: if swallowed can enter lungs and cause damage. Overexposure by

inhalation can cause headaches, nausea, dizziness, decreased blood pressure. Can cause defatting of skin tissue. Prolonged contact may cause painful stinging or burning of eyes

Revision Date: 25-Sep-2013

and lids, watering of eye, and irritation.

## 4.3. Indication of any Immediate Medical Attention and Special Treatment Needed

Notes to Physician Treat symptomatically.

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1. Extinguishing Media

### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### **Unsuitable Extinguishing Media**

Not determined

# 5.2. Special Hazards Arising from the Substance or Mixture

Aerosol flame projection test: >18" extension at 70 F Aerosols are under pressure Aerosols may rupture violently at temperatures above 120 F Vapors may form explosive mixtures with air

# 5.3. Advice for Firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

#### **Personal Precautions**

Use personal protective equipment as required. Remove all sources of ignition.

### For Emergency Responders

Use personal protection recommended in Section 8.

## 6.2. Environmental Precautions

Collect spillage.

## 6.3. Methods and Material for Containment and Cleaning Up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Clean-Up** Place in appropriate containers for disposal.

### 6.4. Reference to Other Sections

See Section 13, Disposal Considerations, for additional information.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1. Precautions for Safe Handling

### Advice on Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Do not spray near open flame. Pressurized container: Do not pierce or burn, even after use. Do not drop. Avoid over-spraying onto floors-slippery surface may result.

# **General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice.

## 7.2. Conditions for Safe Storage, Including any Incompatibilities

### **Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Do not store at temperatures above 120°F. Do not handle or store near any sources of ignition. Store locked up.

### 7.3. Specific End Use(s)

### Specific Use(s)

Cover stains and blemishes.

# Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# 8.1. Control Parameters

# **Exposure Limits**

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Hexane 110-54-3	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	STEL: 60 ppm STEL: 216 mg/m³ TWA: 20 ppm TWA: 72 mg/m³	TWA: 20 ppm TWA: 72 mg/m³ TWA: 1000 mg/m³ STEL: 1500 mg/m³	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 180 mg/m³ Ceiling / Peak: 400 ppm Ceiling / Peak: 1440 mg/m³
Propylene glycol monomethyl ether acetate 108-65-6	S* TWA 50 ppm TWA 275 mg/m³ STEL 100 ppm STEL 550 mg/m³	STEL: 100 ppm STEL: 548 mg/m <sup>3</sup> TWA: 50 ppm TWA: 274 mg/m <sup>3</sup> Skin	TWA: 50 ppm TWA: 275 mg/m³ STEL: 100 ppm STEL: 550 mg/m³	S* STEL: 100 ppm STEL: 550 mg/m <sup>3</sup> TWA: 50 ppm TWA: 275 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 270 mg/m³ Ceiling / Peak: 50 ppm Ceiling / Peak: 270 mg/m³
Iron(III) oxide 1309-37-1		STEL: 10 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	Skin
Component	Italy	Portugal	Netherlands	Finland	Denmark
Hexane 110-54-3 ( 57-63 )	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>	TWA: 50 ppm	STEL: 144 mg/m <sup>3</sup> TWA: 72 mg/m <sup>3</sup>	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup> Skin	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>
Stoddard solvent 8052-41-3 ( 1-5 )		TWA: 100 ppm			TWA: 25 ppm TWA: 145 mg/m <sup>3</sup>
Propylene glycol monomethyl ether acetate 108-65-6 ( 1-5 )	TWA: 50 ppm TWA: 275 mg/m³ STEL: 100 ppm STEL: 550 mg/m³ Skin		TWA: 550 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 270 mg/m³ STEL: 100 ppm STEL: 550 mg/m³ Skin	TWA: 50 ppm TWA: 275 mg/m³ Skin
Iron(III) oxide 1309-37-1 ( 1-5 )		TWA: 5 mg/m <sup>3</sup>		TWA: 5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
Hexane 110-54-3	STEL 80 ppm STEL 288 mg/m³ TWA: 20 ppm TWA: 72 mg/m³	Skin STEL: 400 ppm STEL: 1440 mg/m <sup>3</sup> TWA: 50 ppm TWA: 180 mg/m <sup>3</sup>	TWA: 72 mg/m <sup>3</sup> Skin	TWA: 20 ppm TWA: 72 mg/m³ TWA: 40 ppm TWA: 275 mg/m³ STEL: 30 ppm STEL: 108 mg/m³ STEL: 60 ppm STEL: 343.75 mg/m³	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>
Stoddard solvent 8052-41-3			STEL: 900 mg/m <sup>3</sup> TWA: 300 mg/m <sup>3</sup>		TWA: 100 ppm TWA: 573 mg/m <sup>3</sup>
Propylene glycol monomethyl ether acetate 108-65-6	Skin STEL 100 ppm STEL 550 mg/m³ TWA: 50 ppm TWA: 275 mg/m³	STEL: 50 ppm STEL: 275 mg/m <sup>3</sup> TWA: 50 ppm TWA: 275 mg/m <sup>3</sup>	STEL: 520 mg/m <sup>3</sup> TWA: 260 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 270 mg/m³ Skin STEL: 75 ppm STEL: 337.5 mg/m³	TWA: 50 ppm TWA: 275 mg/m³ STEL: 100 ppm STEL: 550 mg/m³ Skin
Iron(III) oxide 1309-37-1	STEL 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup> STEL: 6 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>

Revision Date: 25-Sep-2013

8.2. Exposure Controls

**Engineering Controls** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

**Eye/Face Protection** Proper eye care is needed in all industrial operations.

**Hand Protection** Gloves are not required for normal use.

**Skin and Body Protection** Suitable protective clothing. **Respiratory Protection** Provide adequate ventilation.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

(1=Water)

9.1. Information on Basic Physical and Chemical Properties

**Physical State** Aerosol **Appearance** Aerosols Odor Not determined Color Dark brown **Odor Threshold** Not determined

Property Values Remarks • Method

На Not determined **Meltina Point/Freezina Point** < -40 °C / <-40 °F **Boiling Point/Boiling Range** 39-40 °C / 103-104 °F Flash Point Not determined

**Evaporation Rate** Fast

Flammability (Solid, Gas) Flammable aerosol

Flammability Limits in Air

**Upper Flammability Limits** 7.5% **Lower Flammability Limit** 1.2%

**Vapor Pressure** 137 mm Hg @ 21°C (70°F) (Air=1)

**Vapor Density** >1 **Specific Gravity** 0.644 **Water Solubility** Nil

Solubility(ies) Not determined **Partition Coefficient** Not determined **Autoignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

9.2. Other information

**VOC Content (%)** 99%

Density 5.378 weight/gal

# **SECTION 10: STABILITY AND REACTIVITY**

### 10.1. Reactivity

Not reactive under normal conditions

### 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of Hazardous Reactions

## **Hazardous Polymerization**

Hazardous polymerization does not occur.

# **Possibility of Hazardous Reactions**

None under normal processing.

# 10.4. Conditions to Avoid

Avoid temperatures above 120°F. Avoid direct sunlight.

## 10.5. Incompatible Materials

Oxidizers.

# 10.6. Hazardous Decomposition Products

None under normal use conditions.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information on Toxicological Effects

## **Acute Toxicity**

# **Product Information**

**Eye Contact** Causes serious eye irritation.

**Skin Contact** Causes skin irritation.

Inhalation Avoid breathing vapors or mists.

Ingestion Do not taste or swallow.

**Unknown Acute Toxicity** 

4.3% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS

document

Oral LD50 35,593.00 **UNITS** mg/kg 4,888.00 Dermal LD50 **UNITS** mg/kg

Inhalation Vapor

80,000.00 UNITS mg/L

Component Information

Component information			
Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Propylene glycol monomethyl ether acetate	= 8532 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	
Iron(III) oxide	> 10000 mg/kg (Rat)		

**Germ cell mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

However, the product as a whole has not been tested.

Chemical Name	European Union
Petroleum gases, liquified, sweetened	Carc. 1B
Stoddard solvent	Carc. 1B

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Symptoms** Please see section 4 of this SDS for symptoms.

**Aspiration hazard** May be fatal if swallowed and enters airways.

# **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

Toxic to aquatic life with long lasting effects

Chemical Name	Algae/aquatic plants	Fish	Crustacea	
Hexane		2.1 - 2.98: 96 h Pimephales	1000: 24 h Daphnia magna mg/L	
		promelas mg/L LC50 flow-through	EC50	
Propylene glycol monomethyl ether		161: 96 h Pimephales promelas	500: 48 h Daphnia magna mg/L	
acetate		mg/L LC50 static	EC50	

# 12.2. Persistence and Degradability

Not determined.

# 12.3. Bioaccumulative Potential

Chemical Name	Partition Coefficient
Petroleum gases, liquified, sweetened	2.8
Propylene glycol monomethyl ether acetate	0.43

# 12.4. Mobility in Soil

# Mobility

Not determined.

## 12.5. Results of PBT and vPvB Assessment

Not determined.

# 12.6. Other Adverse Effects

Not determined

# **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1. Waste Treatment Methods

Waste from Residues / Unused

**Products** 

Disposal should be in accordance with applicable regional, national and local laws and

Revision Date: 25-Sep-2013

regulations.

**Contaminated Packaging** Improper disposal or reuse of this container may be dangerous and illegal.

# SECTION 14: TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances

<u>IMDG</u>

UN1950 14.1 **UN/ID No Proper Shipping Name** 14.2 Aerosols **Hazard Class** 14.3 2.1

14.4

14.5 Marine Pollutant This material may meet the definition of a marine pollutant

14.6 14.7

RID

**UN/ID No** 14.1 UN1950 14.2 Proper Shipping Name Aerosols 2.1

**Hazard Class** 14.3

14.4 14.5

14.6

ADR

14.1 UN/ID No UN1950

14.2 Proper Shipping Name Aerosols, flammable

14.3 **Hazard Class** 2.1

14.4

14.5

14.6

ICAO (air)

14.1 UN/ID No UN1950

14.2 Proper Shipping Name Aerosols, flammable

14.3 Hazard Class 2.1

14.4

14.5

14.6

IATA

**UN/ID No** 14.1 UN1950

14.2 Proper Shipping Name Aerosols, flammable

14.3 Hazard Class 2.1

14.4

14.5

14.6

# **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

# Occupational Illnesses (R-463-3, France)

Chemical Name	French RG number	Title
Hexane 110-54-3	RG 59,RG 84	
Stoddard solvent 8052-41-3	RG 84	
Propylene glycol monomethyl ether acetate 108-65-6	RG 84	
Iron(III) oxide 1309-37-1	RG 44,RG 44bis,RG 94	

# **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

# **International Inventories**

TSCA EINECS/ELINCS DSL/NDSL PICCS ENCS IECSC AICS KECL -

### Legend

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

# 15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier

# **SECTION 16: OTHER INFORMATION**

## Full text of R-phrases referred to under sections 2 and 3

R11 - Highly flammable

R67 - Vapors may cause drowsiness and dizziness

R62 - Possible risk of impaired fertility

R38 - Irritating to skin

R10 - Flammable

R45 - May cause cancer

R46 - May cause heritable genetic damage

R65 - Harmful: may cause lung damage if swallowed

R12 - Extremely flammable

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation

# Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation

H361f - Suspected of damaging fertility

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H304 - May be fatal if swallowed and enters airways

H411 - Toxic to aquatic life with long lasting effects

H225 - Highly flammable liquid and vapor

H361 - Suspected of damaging fertility or the unborn child

H226 - Flammable liquid and vapor

H220 - Extremely flammable gas

H340 - May cause genetic defects

H350 - May cause cancer

#### **Classification Procedure**

Calculation method

Issue Date01-Aug-2013Revision Date:25-Sep-2013Revision NoteNew format.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006, as amended by Regulation (EU) No. 453/2010

# Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**