

SAFETY DATA SHEET

753146 ALBERTA LTD. O/A ULTRASOL INDUSTRIES 10755-69 Avenue NW, Edmonton, Alberta T6H 2C9 Phone: 780-432-6535 Fax: 780-436-6646 E-Mail: Doktordoom@Shaw.ca www.doktordoom.com Toll Free Phone 1-800-452-0023

1. Identification

Product number 1000031968 Item #11606, 66305

Product identifier 450 G ULTRASOL DOKTOR DOOM SURFACE RESIDUAL INSECT KILLER

Company information 753146 Alberta Ltd. o/a Ultrasol Industries

10755 69th Ave NW

Edmonton, AB T6H 2C9 Canada

 Company phone
 1-800-452-0023

 Emergency telephone US
 1-866-836-8855

 Emergency telephone outside
 1-952-852-4646

US

Version # 01

Recommended use Pesticide **Recommended restrictions** None known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSensitization, skinCategory 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May cause an allergic skin reaction.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Distillates (petroleum), Hydrotreated Light		64742-47-8	2.5 - 10

Chemical name	Common name and synonyms	CAS number	<u></u>
White Mineral Oil		8042-47-5	2.5 - 10
Permethrin		52645-53-1	0.1 - 1
Other components below	reportable levels		60 - 80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders. Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. May cause an allergic skin reaction. Dermatitis. Rash.

Most important

treatment needed

symptoms/effects, acute and

delayed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. medical attention and special

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

General fire hazards

Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move

containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

LIC OCHY Table	7-1 Limite for	Air Contaminante	(29 CFR 1910.1000)
US. USHA Table	Z- I LIMITS TOR	' Air Contaminants	(29 CFK 1910.1000)

Components	Type `	, Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	_
		1000 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

controls

Appropriate engineering

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove Hand protection

supplier.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. Aerosol. **Form** Not available. Color Odor Not available.

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.

Initial boiling point and boiling

232.02 °F (111.12 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate
Not available.

Flammability (solid, gas)
Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.9 % estimated

(%)

Flammability limit - upper

9.5 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 80 - 92 psig @20C estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Flammability class Flammable IB estimated
Heat of combustion (NFPA 16.15 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Specific gravity 0.858 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardousHazardous polymerization does not occur.

reactions

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

May cause an allergic skin reaction. **Acute toxicity Test Results** Components **Species** Butane (CAS 106-97-8) **Acute** Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) **Acute Dermal** LD50 Rabbit > 2000 mg/kg > 2000 mg/kg, 24 Hours Inhalation LC50 Rat > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours Oral LD50 Rat > 5000 mg/kg Propane (CAS 74-98-6) **Acute** Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l 658 mg/l/4h White Mineral Oil (CAS 8042-47-5) Acute Dermal LD50 Rabbit > 2000 mg/kg, 24 Hours Inhalation

LC50 Rat 2.18 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Permethrin (CAS 52645-53-1) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Permethrin (CAS 52645-53-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	0.0006 - 0.0025 mg/l, 48 hours

Apache trout (Oncorhynchus gilae

Persistence and degradability No data is available on the degradability of this product.

apache)

Bioaccumulative potential

Fish

Partition coefficient n-octanol / water (log Kow)

Butane 2.89 Permethrin 6.5 Propane 2.36

LC50

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

0.0013 - 0.0022 mg/l, 96 hours

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 306 Packaging exceptions

^{*} Estimates for product may be based on additional component data not shown.

Packaging non bulk None Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Not applicable. Packing group

Environmental hazards Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number **UN** proper shipping name

Transport hazard class(es)

UN1950 **AEROSOLS**

Class 2.1 Subsidiary risk Label(s) 2.1

Not applicable. Packing group

Environmental hazards

Marine pollutant Yes F-D. S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

LTD QTY Not applicable.

DOT



IATA; IMDG



Marine pollutant



General information DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Permethrin	52645-53-1	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

FIFRA Information

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The pesticide label also includes other important information, including directions for use.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region

, ,		, ,,	,
Australia	Australian Inventory of Chemical Substances (AICS)		Yes
Canada	Domestic Substances List (DSL)		No
Canada	Non-Domestic Substances List (NDSL)		No
China	Inventory of Existing Chemical Substances in China (IECSC)		Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)		No
Europe	European List of Notified Chemical Substances (ELINCS)		No
Japan	Inventory of Existing and New Chemical Substances (ENCS)		No
Korea	Existing Chemicals List (ECL)		Yes
New Zealand	New Zealand Inventory		Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)		Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory		No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Inventory name

Issue date 11-26-2018

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

On inventory (yes/no)*