

Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

* 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses of the substance or mixture
Marking spray

1.3 Details of the supplier of the safety data sheet

Albert Kerbl GmbH
Felizenzell 9
D-84428 Buchbach
www.kerbl.com
Tel.: 0049-(0)8086-933-100
E-Mail: info@kerbl.com

Responsible Department:

Albert Kerbl GmbH
Tel.: 0049-(0)8086-933-104
E-Mail: bm@kerbl.com

1.4 Emergency telephone number:

Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen,
Sachsen-Anhalt und Thüringen
c/o HELIOS Klinikum Erfurt Nordhäuser Straße 74
Tel.: (03 61) 73 07 30 - Fax: (03 61) 7 30 73 17
E-Mail: ggiz@ggiz-erfurt.de - Internet: www.ggiz-erfurt.de

* 2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) Nr. 1272/2008

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3 (H412)

Classification according to Directives 67/548/EEC and 1999/45/EC

F+ - Extremely flammable,

Xi - Irritant



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

2.2 Label elements

Label elements according to Regulation (EC) Nr. 1272/2008 (CLP/GHS)

Hazard pictograms



Flame (GHS 02)



Exclamation mark (GHS07)

Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.
P403 Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to waste disposal site in accordance with local/national regulations.

Label elements according to Directives 67/548/EEC and 1999/45/EC

F+ - Extremely flammable, Xi - Irritating

Risk phrases

R12 Extremely flammable.
R36 Irritating to eyes.
R67 Vapours may cause drowsiness and dizziness.

Safety phrases

S2 Keep out of the reach of children.
S16 Keep away from sources of ignition - No smoking.
S23 Do not breathe aerosol
S51 Use only in well-ventilated areas.

2.3 Other hazards

· None



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

3 Composition/information on ingredients

Chemical Characterization: Mixtures

Hazardous ingredients:

CAS: 67-63-0	2-PROPANOL	30-60 %
EC-Nr. 200-661-7	F ; R11 Xi ; R36 R67	
Index-Nr. 603-117-00-0	Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336	
CAS: 548-62-9	C. I. Basic Violet 3	<1 %
EC-Nr. 208-953-6	Carc. 2;H351; Acute tox. 4;H302; Eye Dam. 1;H318;	
Index-Nr. 612-204-00-2	Aquatic Acute 1;H400; Aquatic Chronic 1;H410;	
	Carc. Cat. 3; R40 Xn; R22 Xi; R41 N; R50/53	

Additional information:

The wording of the listed risk phrases and hazard statements refer to section 16.

4 First aid measures

4.1 Description of first aid measures

· **General information:**

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

· **Inhalation:**

Move to fresh air. If symptoms persist, call a physician.

· **Skin contact:**

Remove immediately any soiled or splashed garment. Rinse abundantly in the water and in the soap. Clean clothes separately before reusing them. Consult a doctor in case of persistent pain.

· **Eye contact:**

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open. If there is any redness, pain or visual impairment, consult an ophthalmologist.

· **Ingestion:**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Keep the person exposed at rest. Do not force vomiting. Seek medical attention, showing the label. If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation of spray mist is irritating to the upper airways.

4.3 Indication of any immediate medical attention and special treatment needed

None



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: Marking spray TopMarker blue

Product codes: 20123, 20149, 20158

5 Firefighting measures

5.1 Extinguishing media

Suitable methods of extinction - In the event of a fire, use: sprayed water or water mist, foam, multipurpose ABC powder, BC powder, carbon dioxide (CO₂)

Unsuitable methods of extinction - In the event of a fire, do not use: water jet

5.2 Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke. In the event of a fire, the following may be formed: carbon monoxide (CO), carbon dioxide (CO₂)

5.3 Advice for firefighters

Special protective equipment: Wear self-contained breathing apparatus.

Further information

Cool endangered containers with water spray jet.

Dispose fire residues and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non fire-fighters: Avoid any contact with the skin and eyes.

For fire-fighters: Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

6.2 Environmental precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal. Prevent any material from entering drains or waterways.

6.3 Methods and material for containment and cleaning up:

Clean preferably with a detergent, do not use solvents.

6.4 Reference to other sections

Informationen regarding safe handling see chapter 7.

Informationen regarding personal protection see chapter 8.

Informationen regarding disposal see chapter 13.



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

7 Handling and storage

7.1 Precautions for safe handling

Ensure that there is adequate ventilation, especially in confined areas.

Open and handle container with care.

Fire prevention:

Keep ignition sources away - Do not smoke. Take precautionary measures against static discharges. Pressurized container. Protect from sunlight and temperatures above 50 ° C (eg by Electric lights). Do not open by force or burn even after use. Do not spray in flames or on hot surfaces.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements for storage rooms and vessels:

Store in a cool place.

Official regulations on storing pressurized containers must be observed.

Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly closed.

Not keep the container sealed.

Store in tightly closed containers in a cool, dry place.

Protect from heat and direct sunlight.

Recommended storage temperature: 5-30 ° C

Storage class: No data available.

7.3 Specific end use(s) Keep out of reach of children.

8 Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits		Exposure			
	Country	limit	ml/m³	mg/m³	Remarks
64-17-5 Ethanol	D, TRGS 900	AGW	500	960	2(II);DFG, Y
	UK, WEL	TWA	1000	1920	8 h
	F, INRS	VME	1000	1900	8 h
		VLE	5000	9500	15 min
106-97-8 Butan	D, TRGS 900	AGW	1000	2400	4(II);DFG
	UK, WEL	TWA	600	1450	8 h
		STEL	750	1810	15 min
	F, INRS	VME	800	1900	8 h
67-63-0 Propan-2-ol	D, TRGS 900	AGW	200	500	2(II);DFG, Y
	UK, WEL	TWA	400	999	8 h
		STEL	500	1250	15 min
	F, INRS	VLE	400	980	15 min
74-98-6 Propan	D, TRGS 900	AGW	1000	1800	4(II);DFG
	UK, WEL	TWA	1000	1800	8 h
75-28-5 Isobutan	D, TRGS 900	AGW	1000	2400	4(II);DFG



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

Biological limits	Country	mg/l	Remarks
67-63-0 Propan-2-ol	D, TRGS 903	25	Acetone, Blood, end of shift/exposure
		25	Acetone, Urine, end of shift/exposure

8.2 Exposure controls / Personal protection

Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

Eye / face protection

Avoid contact with eyes. Use eye protectors designed to protect against liquid splashes. Before handling, wear safety goggles with protective sides in accordance with standard EN166. In the event of high danger, protect the face with a face shield. When spraying, wear a face shield in accordance with standard EN166. Prescription glasses are not considered as protection. Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours. Provide eyewash stations in facilities where the product is handled constantly.

Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact. Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374. Gloves must be selected according to the application and duration of use at the workstation. Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

Skin protection (other than of the hands)

Work clothing worn by personnel shall be laundered regularly. After contact with the product, all parts of the body that have been soiled must be washed.

Respiratory protection

In case of insufficient ventilation, wear respiratory protective equipment with filter.

Thermal hazards

No data available.

Exposure controls regarding environmental protection

No data available.



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:

Aerosol

Colour:

blue

Odour:

Alcohol

Smell Threshold:

not determined

pH:

not determined

Change of state

Melting point/range:

not relevant

Boiling point/range:

< 35°C

Flash point:

-97°C

Flammability (solid, gas):

not applicable

Ignition temperature:

365°C

Thermal decomposition:

not relevant

Autoinflammability:

not self-flammable

Explosion hazard:

not determined

Explosion limits:

Lower:

1,3 Vol %

Upper:

15,0 Vol %

Vapour pressure at 20 °C:

not determined

Density:

not determined

Bulk density

not determined

Vapour density

not determined

Evaporation rate

not determined

Solubility / miscibility

Water:

not or little miscible.

Partition coefficient (n-Octanol/Water):

not determined

Viscosity:

not determined

9.2 Other information

No data available.

10 Stability and reactivity

10.1 Reactivity No data available.

10.2 Chemical stability This mixture is stable under the recommended handling and storage conditions in section 7.

10.3 Possibility of hazardous reactions No hazardous reactions when stored under the recommended handling and storage conditions.

10.4 Conditions to avoid:

Sunlight

High temperatures.

10.5 Incompatible materials: Reacts with strong oxidants.

10.6 Hazardous decomposition products: None when used as intended.



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

67-63-0 2-PROPANOL

Oral	LD-50	5,84 mg/kg (Rat)
Dermal	LD-50	16,4 mg/kg (Rabbit)
Inhalation	LC50	> 10000 ppm (Rat, 6h)

Primary irritating effect:

- **Skin corrosion/skin irritation:** Slight irritation is not ruled out, based on the product composition.
- **eye irritation:** Slight irritation is not ruled out, based on the product composition.

Sensitisation: No sensitizing effects known.

Germ cell mutagenicity/Carcinogenicity/Reproductive toxicant: Contains C. I. Basic Violet 3: Suspected of causing cancer.

Specific target organ systemic toxicity - single/repeated exposure: No effects known.

Aspiration hazard: No effects known.

Additional toxicological information: Inhalation of concentrated vapors as well as oral intake will lead to anesthesia-like conditions and headache, dizziness, etc.
Has a degreasing effect on the skin!

12 Ecological information

12.1 Toxicity

Aquatic Toxicity:

67-63-0 2-PROPANOL

LC-50	10000 mg/l (Fisch, 96 h)
LC-50	>10000 mg/l (Daphnia, 24h)

548-62-9 C. I. Basic Violet 3

EC-50	0,025-0,8 mg/l (Algae, 72 h)
EC-50	0,24-0,5 mg/l (Daphnia, 48 h)

12.2 Persistence and degradability Readily biodegradable.

12.3 Bioaccumulative potential The product is not bioaccumulative.

12.4 Mobility in soil No data available.

12.5 Results of PBT and vPvB assessment The mixture does not meet the criteria for PBT or vPvB.

12.6 Other adverse effects No data available.

Additional ecological information Harmful to aquatic life with long lasting effects.



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: **Marking spray TopMarker blue**

Product codes: 20123, 20149, 20158

13 Disposal considerations

13.1 Waste treatment methods

Recommendation:

Must not be disposed together with household garbage. Do not empty into drains.

Must be supplied to an authorized hazardous waste incineration plant, after pretreatment, in accordance with regulations for special waste.

European waste catalog

The listed (n) waste number (s) according to the European Waste Catalogue (EWC), are a recommendation. A final decision must be taken in agreement with the regional waste management company.

16 05 04* gases in pressure containers, containing hazardous substances (including halons)

Uncleaned packaging:

Recommendation: Disposal according to official regulations.

14 Transport information

14.1 UN number

· ADR/RID, ADN, IMDG, ICAO/IATA

UN1950

14.2 UN proper shipping name

· ADR/RID, ADN

AEROSOLS

· IMDG

AEROSOLS

· ICAO/IATA

AEROSOLS, flammable

14.3 Transport hazard class(es)

· ADR/RID, ADN, IMDG, ICAO/IATA

2.1

Classification code

· ADR/RID, ADN

5F

Special Provisions

· ADR/RID, ADN

190, 327, 344, 625

· IMDG

63, 190, 277, 327, 344, 959

· ICAO/IATA

A145, A167, A802

14.4 Packing group

none

14.5 Environmental hazards

none

14.6 Special precautions for user

EmS

F-D, S-U

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 13.05.2015

Revision number 1.2

Version date: 13.05.2015

Product name: Marking spray TopMarker blue

Product codes: 20123, 20149, 20158

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

None

National Regulations

Germany: Wassergefährdungsklasse (WGK)

Klasse : 1 (Schwach wassergefährdend) Einstufung gemäß VwVwS

15.2 Chemical safety assessment: No data available

16 Other information

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Revision notes

* Changes since the last version

Abbreviations

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

Title for H, EUH and R indications (Number and text)

H222 - Extremely flammable aerosol.

H225 - Highly flammable liquid and vapour.

H229 - Pressurized container: May burst if heated.

H302 - Harmful if swallowed.

H318 - Causes serious eye damage.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H351 - Suspected of causing cancer.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

H412 - Harmful to aquatic life with long lasting effects.

R11 - Highly flammable.

R12 - Extremely flammable.

R22 - Harmful if swallowed.

R36 - Irritating to eyes.

R40 - Limited evidence of a carcinogenic effect.

R41 - Risk of serious damage to eyes.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 - Vapours may cause drowsiness and dizziness.

Methods of evaluating information referred to in Article 9 of Regulation (EC) No 1272/2008 for the purpose of classification

Classification based on the components