

P.O. Box 1000 Bensenville, IL 60106 800-762-4242 Fax 630-766-6000

# MATERIAL SAFETY DATA SHEET (MSDS) **PRODUCT NAME: Original Premium Poultice**

**UPDATES: 6/24/11 - 2/9/2012** PREP'D BY: Nick Cinquino



# **SECTION 1: PRODUCT IDENTIFICATION**

Product Name: Original Premium Clay

Synonyms: None

Finish Line Product #: 06

Product Type: Poultice for horses

#### **SECTION 2: INGREDIENTS**

Aluminum silicate, Montmorillonites, Water, Boric acid, Glycerine, Salicylic acid, Methyl salicylate, Eucalyptus oil, Peppermint oil.

NOTE: Actual ingredient percentages are proprietary.

# **SECTION 3: PHYSICAL DATA**

Appearance:

Light tan, heavy clay/water.

Solubility: Odor:

Disperses in water. Peppermint odor.

Boiling Point/Melting Point:

Does not boil. Does not melt.

#### **SECTION 4: FIRE AND EXPLOSION HAZARD DATA**

Flash Point:

Does not flash below 212 F

Extinguishing Media:

N/A.

Other required equipment:

Face mask.

Other Notes:

# SECTION 5: TECHNICAL ASSISTANCE AND EMERGENCY INFORMATION

Contact: Nick Cinquino

PHONE# 630-694-0000 8:00AM-4:30PM Central Time

EMAIL:

Finishlinehorse@ameritech.net

## **SECTION 6: HEALTH HAZARD DATA**

EYES: SKIN:

Flush eyes with clean water.

Rinse off with water.

RESPIRATORY:

N/A.

#### SECTION 7: CHEMICAL REACTIVITY DATA

STABILITY:

CONDITIONS TO AVOID:

INCOMPATIBLE CHEMICALS:

HAZARDOUS DECOMPOSITION PRODUCTS:

CORROSIVE TO METALS?

Stable. Store in a cool, dry place, out of direct sunlight. Open flame, heat, sparks or other sources of ignition.

N/A

N/A

No.

# SECTION 8:SPECIAL PROTECTION INFORMATION

PREVENTION:

RESPIRATORY:

**VENTILATION:** 

EYE:

CLOTHING:

Keep all containers sealed to prevent hazards

Use dust mask if needed.

Provide proper ventilation.

Use goggles to protect eyes from contact.

Use protective clothing if in contact with material for extended periods.

## **SECTION 9: ENVIRONMENTAL PROTECTION**

ENVIRONMENTAL TOXICITY DATA SPILL AND LEAK PROCEDURES

WASTE DISPOSAL

Nontoxic, biodegradable.

Sweep up and dispose of properly.

Dispose of according to local regulations for non-toxic clays.

# **SECTION 10: SHIPPING DATA**

D.O.T. Shipping Name Bill Of Lading Description

Special Labeling

Clay Clay

N/A

**SECTION 11: LABEL FACSIMILE** 

Finish Line®'s ORIGINAL PREMIUM POULTICE™ is unbeatable with its easy on/off application

RECOMMENDED USES: As an aid in the temporary relief of minor screness and stiffness due to overexertion in horse's legs and feet.

Directions: For tightening legs only: Cleanse affected area thoroughly. Apply Original Premium Poultica<sup>10</sup> liberally (1/8" to 1/4" thick), Finally, cover with a thin layer of gauze or cheesecloth, and standing bandage. Remove bandages and poultice after 24 hours, rinse with cold water, repeat as

Cleanse affected area thoroughly. Apply Original Premium Positice\*\* liberally (1/8\* to 1/4\* thick). Always cover with a sheet of cotton first, then cover with plastic wrap or paper. Next, use cotton or a quilted wrap. Finally, cover with a standing bandage Remove bandages and poultice after 24 hours, rinse with cold water, repeat as needed.

As a hoof packing for minor heat and inflammation: Clean underside of hoof thoroughly. Apply a small handful of Original Premium Poulfice<sup>16</sup> to underside of hoof and cover with kraft paper.

@2011 Finish Line® Horse Products, Inc. All Rights Reserved

Extra Soothing and Cooling

PRODUCT FACTS (cont'd)

Ingredients: A superior Aluminum silicate blended with Montmorfillonites, Purified water, Boric Acid, Glycerine, Salicylic Acid, Methyl Salicylate, Eucalyptus Oil, Peppermint Oil.

- For external equine use only.
  Avoid contact with eyes and mucous membranes.
  Store in a cool (60-80° F) place.
  Keep out of reach of children.
  Not for use on horses intended for food.

100% Satisfaction Guaranteed Questions? Comments? Call 800-762-4242 Mon.-Fri. 8 a.m. to 4:30 p.m. Central Tim

de in the USA by: sh Line® Horse Products, Inc senville, IL 60108



Quality Horse Products

Horse Products, Inc.

Quality...A Family Tradition

Net Wt. 23 lb. (10.45 kg.)