Safety Data Sheet



Superior Equine Grooming Products

1.800.982.2017 | shapleys.com

	Date	01-Aug-2013
122ne	Dale	01-Aug-2013

Revision Date: 25-Sep-2013

Version 1

	
	1. IDENTIFICATION
Product Identifier	
Product Name	Show Touch Up-Medium Brown
Other means of identification	
SDS #	55072
UN/ID No	UN1950
Product Code	STU-MB
Other Information	Formula: 55072.
Recommended use of the chemical	and restrictions on use
Recommended Use	Cover stains and blemishes.
Details of the supplier of the safety	data sheet
Supplier Address	
Shapley's	
11650 Chitwood Dr.	
Fort Myers, FL 33908	
www.shapleys.com	
Emergency Telephone Number	
Company Phone Number	Phone: 239-415-2275
	Fax: 239-415-2277

Emergency Telephone (24 hr)

Findle: 239-415-2275 Fax: 239-415-2277 INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Aerosols

Physical State Aerosol

<u>Classification</u>	
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard Statements

Causes skin irritation Causes serious eye irritation May cause genetic defects May cause cancer Suspected of damaging fertility or the unborn child May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Extremely flammable aerosol



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do not induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

4.7% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Hexane	110-54-3	57-63
Petroleum gases, liquified, sweetened	68476-86-8	27-33
Yellow Iron Oxide	51274-00-1	1-5
Propylene glycol monomethyl ether acetate	108-65-6	1-5
Iron(III) oxide	1309-37-1	1-5

4. FIRST-AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.	
Eye Contact	If adverse effects occur, rinse eyes with large amounts of water until irritation subsides. If eye irritation persists: Get medical advice/attention.	
Skin Contact	Wash with soap and water. Apply hand cream. Get medical attention if irritation occurs. Take off contaminated clothing. Wash contaminated clothing before reuse.	
Inhalation	Remove to fresh air.	
Ingestion	Do not induce vomiting. Call a physician or poison control center immediately.	
Most important symptoms and effects		

Symptoms Aspiration hazard: if swallowed can enter lungs and cause damage. Overexposure by inhalation can cause headaches, nausea, dizziness, decreased blood pressure. Can cause defatting of skin tissue. Prolonged contact may cause painful stinging or burning of eyes and lids, watering of eye, and irritation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Aerosol flame projection test: >18" extension at 70 F. Aerosols are under pressure. Aerosols may rupture violently at temperatures above 120 F. Vapors may form explosive mixtures with air.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition.	
Environmental Precautions	See Section 12 for additional Ecological Information.	
Methods and material for containment and cleaning up		
Methods for Containment	Prevent further leakage or spillage if safe to do so.	
Methods for Clean-Up	Keep in suitable, closed containers for disposal.	

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Do not spray near open flame. Pressurized container: Do not pierce or burn, even after use. Do not drop. Avoid over-spraying onto floors-slippery surface may result.

Conditions for safe storage, including any incompatibilities

Storage ConditionsKeep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct
sunlight. Do not store at temperatures above 120°F. Do not handle or store near any
sources of ignition. Store locked up.

Incompatible Materials Oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m ³
		(vacated) TWA: 180 mg/m ³	_
Iron(III) oxide	TWA: 5 mg/m ³ respirable	TWA: 10 mg/m ³ fume	IDLH: 2500 mg/m ³ Fe dust and
1309-37-1	fraction	TWA: 15 mg/m ³ total dust	fume
		TWA: 5 mg/m ³ respirable	TWA: 5 mg/m ³ Fe dust and fume
		fraction	-
		(vacated) TWA: 10 mg/m ³ fume	
		and total dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction regulated	
		under Rouge	

Appropriate engineering controls

Engineering Controls	Ensure adequate ventilation, especially in confined areas.		
Individual protection measures, such as personal protective equipment			
Eye/Face Protection	Proper eye care is needed in all industrial operations.		
Skin and Body Protection	Protective gloves are not required, but recommended.		
Respiratory Protection	Ensure adequate ventilation, especially in confined areas.		

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Appearance Color	Aerosol Aerosols Medium brown	Odor Odor Threshold	Not determined Not determined
Property pH Melting Point/Freezing Point Boiling Point/Boiling Range Flash Point Evaporation Rate Flammability (Solid, Gas) Upper Flammability Limits Lower Flammability Limit Vapor Pressure	Values Not determined < -40 °C / <-40 °F 39-40 °C / 103-104 °F Not determined Fast Flammable aerosol 7.5% 1.2% 137 mm Hg	<u>Remarks • Method</u> @ 21°C (70°F)	
Vapor Density Specific Gravity Water Solubility Solubility in other solvents Partition Coefficient Autoignition Temperature Decomposition Temperature Kinematic Viscosity Dynamic Viscosity	>1 0.644 Nil Not determined Not determined Not determined Not determined Not determined	(Air=1) (1=Water)	

Property Explosive Properties Oxidizing Properties VOC Content (%) Density Values Not determined Not determined 96% 5.378 weight/gal

10. STABILITY AND REACTIVITY

Remarks • Method

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid temperatures above 120°F. Avoid direct sunlight.

Incompatible Materials

Oxidizers.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation. May be harmful in contact with skin.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat)4 h
Propylene glycol monomethyl ether acetate 108-65-6	= 8532 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Iron(III) oxide 1309-37-1	> 10000 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

Isobutane is considered a carcinogen when it contains >= 0.1% of 1,3-butadiene.

Chemical Name	ACGIH	IARC	NTP	OSHA
Iron(III) oxide		Group 3		
1309-37-1				
Legend				
ACGIH (American Conference of Governmental Industrial Hygienists)				

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
STOT - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.	
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Numerical measures of toxicity Not determined		
Unknown Acute Toxicity	4.7% of the mixture consists of ingredient(s) of unknown toxicity.	

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hexane 110-54-3		2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through		1000: 24 h Daphnia magna mg/L EC50
Propylene glycol monomethyl ether acetate 108-65-6		161: 96 h Pimephales promelas mg/L LC50 static		500: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Petroleum gases, liquified, sweetened 68476-86-8	2.8
Propylene glycol monomethyl ether acetate 108-65-6	0.43

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status	
Hexane	Toxic	
110-54-3	Ignitable	

14. TRANSPORT INFORMATION

<u>Note</u>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.	
DOT_ UN/ID No Proper Shipping Name Hazard Class	UN1950 Aerosols 2.1	
<u>IATA</u> UN/ID No Proper Shipping Name Hazard Class	UN1950 Aerosols, flammable 2.1	
IMDG UN/ID No Proper Shipping Name Hazard Class Marine Pollutant	UN1950 Aerosols 2.1 This material may meet the definition of a marine pollutant	

15. REGULATORY INFORMATION

International Inventories

TSCA

Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexane	5000 lb		RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ

<u>SARA 313</u>

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	57-63	1.0

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Hexane 110-54-3	Х	X	Х
Iron(III) oxide 1309-37-1	Х	X	Х

16. OTHER INFORMATION

<u>NFPA</u> HMIS	Health Hazards Not determined Health Hazards 2	Flammability Not determined Flammability 4	Instability Not determined Physical Hazards 0	Special Hazards Not determined Personal Protection B
Issue Date Revision Date: Revision Note	01-Aug-2013 25-Sep-2013 New format			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet