SAFETY DATA SHEET

1. Identification

Product identifier	B57901 KONK 400 INSECTIC	IDE WITH BAYGON
Other means of identification		
Product code	1000016703	
Recommended use	PESTICIDE	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name	ACUITY HOLDINGS INC. dba	AMREP
Address	11627 178 STREET NW	
	EDMONTON, AB T5S 1N6	
	Canada	
Telephone	General Assistance	1-905 669-9876
E-mail	Not available.	
Emergency phone number	Emergency - US	1-866-836-8855
	Emergency - Outside US	1-952-852-4646
Supplier	Not available.	

..

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, inhalation	Category 4
	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity	Category 1B
	Aspiration hazard	Category 1

Label elements



Signal word	Danger		
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation. Harmful if inhaled. May damage fertility or the unborn child.		
Precautionary statement			
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.		
Storage	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Environmental hazards	Hazardous to the aquatic environment, acute Category 1 hazard		
	Hazardous to the aquatic environment, Category 1 long-term hazard		
Other hazards	Combustible.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	51.643
Propane		74-98-6	25
Isopropyl Alcohol		67-63-0	10.5
Piperonyl Butoxide		51-03-6	8.2
n-Methyl-2-Pyrrolidinone		872-50-4	2.5
Propoxur (2-isopropoxyphenyl Methylcarbamate)		114-26-1	2.149
Other components below reportable	e levels		0.009

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	If eye irritation persists: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
monoung any moompandimes	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values Components Value Type Isopropyl Alcohol (CAS STEL 400 ppm 67-63-0) TWA 200 ppm Propoxur TWA 0.5 mg/m3 (2-isopropoxyphenyl Methylcarbamate) (CAS 114-26-1) Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Туре Value Isopropyl Alcohol (CAS STEL 984 mg/m3 67-63-0) 400 ppm TWA 492 mg/m3 200 ppm Propane (CAS 74-98-6) 1000 ppm TWA 0.5 mg/m3 TWA

Propoxur (2-isopropoxyphenyl Methylcarbamate) (CAS 114-26-1)

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components		Туре		V	alue	Form
Propoxur (2-isopropoxyphenyl Methylcarbamate) (CAS 114-26-1)		TWA TWA			00 ppm 9.5 mg/m3	
Canada. Manitoba OELs Components	(Reg. 217/2006, T	he Wo Type	rkplace Safety An	-	/alue	
Isopropyl Alcohol (CAS 67-63-0)		STEL		4	00 ppm	
01 00 0)		TWA		2	00 ppm	
Propoxur (2-isopropoxyphenyl Methylcarbamate) (CAS 114-26-1)		TWA		0	.5 mg/m3	
Canada. Ontario OELs. (Components	Control of Exposu	ire to E Type	Biological or Cher	• ·	/alue	
Isopropyl Alcohol (CAS 67-63-0)		STEL		4	00 ppm	
		TWA			00 ppm	
n-Methyl-2-Pyrrolidinone (CAS 872-50-4)		TWA		4	00 mg/m3	
Propoxur (2-isopropoxyphenyl Methylcarbamate) (CAS 114-26-1)		TWA		0	.5 mg/m3	
Canada. Quebec OELs. (Components	Ministry of Labor	- Regu Type	lation Respecting		of the Work Envi /alue	ronment)
Isopropyl Alcohol (CAS 67-63-0)		STEL		1	230 mg/m3	
07 00 0)				5	00 ppm	
		TWA			83 mg/m3	
		T \A/A			00 ppm	
Propane (CAS 74-98-6)		TWA			800 mg/m3 000 ppm	
Propoxur		TWA			.5 mg/m3	
(2-isopropoxyphenyl Methylcarbamate) (CAS 114-26-1)						
logical limit values						
ACGIH Biological Expose Components	ure Indices Value		Determinant	Specimen	Sampling Tir	ne
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l		Acetone	Urine	*	
n-Methyl-2-Pyrrolidinone (CAS 872-50-4)	100 mg/l		5-Hydroxy-N-m ethyl-2-pyrrolid one	Urine	*	
* - For sampling details, pl	ease see the sourc	e docu				
osure guidelines						
Canada - British Columb	ia OELs: Skin des	ignati	on			
Distillates (Petroleum) 64742-47-8)	, Hydrotreated Lig	nt (CAS	Can be	absorbed thro	ough the skin.	
propriate engineering trols	Provide eyew	ash sta	ition.			
vidual protection measur				-+		

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

er i nyelear ana enemiear j	
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	415.4 °F (213 °C) estimated
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	0.8 % estimated
Flammability limit - upper (%)	7.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	506.8 °F (263.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.784 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage a

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.		
Skin contact	No adverse effects due to skin contact are expected.		
Eye contact	Causes serious eye irritation.		
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.		

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Harmful if inhaled.		
Components	Species	Test Results	
Distillates (Petroleum), Hy	drotreated Light (CAS 64742-47-8)		
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
		> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Rat	> 7.5 mg/l, 6 Hours	
		> 4.6 mg/l, 4 Hours	
Oral			
LD50	Rat	> 5000 mg/kg	
Isopropyl Alcohol (CAS 67	/-63-0)		
Acute			
Dermal			
LD50	Rabbit	16.4 ml/kg, 24 Hours	
Inhalation			
LC50	Rat	> 10000 ppm, 6 Hours	
Oral			
LD50	Rat	5.84 g/kg	
n-Methyl-2-Pyrrolidinone (CAS 872-50-4)		
Acute			
Dermal			
LD50	Rat	> 5000 mg/kg, 24 Hours	
Inhalation			
LC50	Rat	> 5.1 mg/l, 4 Hours	
Oral			
LD50	Rat	4150 mg/kg	
Piperonyl Butoxide (CAS 5	51-03-6)		
<u>Acute</u>			
Dermal			
LD50	-	> 2000 mg/kg	
Inhalation			
LC50	Rat	> 5.2 mg/l, 4 Hours	
Oral			
LD50	Rat	> 2000 mg/kg	

Components	Species			Test Results
Propane (CAS 74-98-6)				
<u>Acute</u>				
Inhalation				
LC50	Mouse			1237 mg/l, 120 Minutes
				52 %, 120 Minutes
	Rat			1355 mg/l
				658 mg/l/4h
* Estimates for product ma	v be based on a	dditional componer	nt data not shown	
Skin corrosion/irritation	-	-	ause temporary irritati	ion.
Serious eye damage/eye	-	ious eye irritation.	. ,	
irritation				
Respiratory or skin sensitizat	ion			
Respiratory sensitization	Not a respi	ratory sensitizer.		
Skin sensitization	This produc	ct is not expected to	o cause skin sensitiza	ition.
Germ cell mutagenicity		ailable to indicate p or genotoxic.	product or any compo	nents present at greater than 0.1% are
Carcinogenicity				
ACGIH Carcinogens				
Isopropyl Alcohol (CAS 67-63-0) Propoxur (2-isopropoxyphenyl Methylcarbamate) (CAS		arbamate) (CAS	A4 Not classifiable as a human carcinogen. A3 Confirmed animal carcinogen with unknown relevance to	
114-26-1) Canada - Manitoba OELs	: carcinogenici	ty	humans.	
2-PROPANOL (CAS 67-63-0) PROPOXUR (CAS 114-26-1)			Not classifiable as a human carcinogen. Confirmed animal carcinogen with unknown relevance to humans.	
IARC Monographs. Overa		f Carcinogenicity		
Piperonyl Butoxide (C	,			s to carcinogenicity to humans.
Reproductive toxicity		May damage fertility or the unborn child.		
Specific target organ toxicity single exposure	 Not classified 	ed.		
Specific target organ toxicity repeated exposure	- Not classifi	ed.		
Aspiration hazard	May be fata	al if swallowed and	enters airways.	
12. Ecological informati				
Ecotoxicity	Very toxic t	•	ong lasting effects.	
Components		Species		Test Results
Distillates (Petroleum), Hyd	Irotreated Light	(CAS 64742-47-8)		
Aquatic Fish	LC50	Rainbow trout, (Oncorhynchus	donaldson trout	2.9 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-	63-0)	Cheomyneilu	5 myr(35)	
Aquatic				
Algae	IC50	Algae		1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia		13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepor	nis macrochirus)	> 1400 mg/l, 96 hours
n-Methyl-2-Pyrrolidinone (0	CAS 872-50-4)	· ·		
Aquatic				
Aquatic Algae	IC50	Algae		500.0001 mg/L, 72 Hours

Components		Species	Test Results
Piperonyl Butoxide (CAS 51-	03-6)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson tro (Oncorhynchus mykiss)	out 0.0027 - 0.0043 mg/l, 96 hours
Propoxur (2-isopropoxypheny	/I Methylcarban	nate) (CAS 114-26-1)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna) 0.0209 - 0.0365 mg/l, 48 hours
Fish	LC50	Brown Trout (Salmo trutta fa	ario) 1.84 - 2.42 mg/l, 96 hours
* Estimates for product may b	be based on add	ditional component data not sh	own.
sistence and degradability	No data is av	ailable on the degradability of	this product.
accumulative potential			
Partition coefficient n-c	octanol / water	(log Kow)	
Isopropyl Alcohol		0.05	
n-Methyl-2-Pyrrolidinone		-0.54	
Piperonyl Butoxide		4.75	
Propane		2.36	
Propoxur (2-isopropoxyp	henyl Methylca	rbamate) 1.52	
bility in soil	No data avai	lahla.	

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation
potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
Special precautions for user	r Read safety instructions, SDS and emergency procedures before handling.
This product meets the exemp	tion requirements and may be shipped as a limited quantity.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes

	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo aircraft	Allowed with restrictions.
	Cargo aircraft only	Allowed with restrictions.
IM	DG	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	
	Marine pollutant	Yes
	EmS	F-D, S-U
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Tra	ansport in bulk according to	Not applicable.
۸r	nex II of MADDOL 72/79 and	

Annex II of MARPOL 73/78 and the IBC Code



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations Controlled Drugs and Substances Act Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed. Greenhouse Gases Not listed. Precursor Control Regulations Not regulated. International regulations

Stockholm Convention		
Not applicable.		
Rotterdam Convention		
Not applicable.		
Kyoto protocol		
Not applicable.		
Montreal Protocol		
Not applicable.		
Basel Convention		
Not applicable.		
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

(PICCS)

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date Version #	05-26-2017 01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names

No