

To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.

SAFETY DATA SHEET

1. Identification

Product identifier	B60401 KONK BLASTER - 350g	
Other means of identification		
Product code	1000016719	
Recommended use	PESTICIDE	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name Address	ACUITY HOLDINGS INC. dba AMREP 11627 178 STREET NW	
	EDMONTON, AB T5S 1N6	
	Canada	
Telephone	General Assistance	1-905 669-9876
E-mail	Not available.	
Emergency phone number	Emergency - US	1-866-836-8855
	Emergency - Outside US	1-952-852-4646
Supplier	Not available.	

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Aspiration hazard	Category 1
Label elements		



	• • • • • • • • • • • • • • • • • • •	
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. May be fatal if s	wallowed and enters airways.
Precautionary statement		
Prevention		ben flames and other ignition sources. No smoking. n source. Do not pierce or burn, even after use.
Response	IF SWALLOWED: Immediately call a POISON	CENTER/doctor. Do NOT induce vomiting.
Storage	Store locked up. Protect from sunlight. Do not	expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
Other hazards	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), Hydrotreated Heavy		64742-48-9	62.313
Propane		74-98-6	20.67
Isobutane		75-28-5	9.33

Chemical name	Common name and synonyms	CAS number	%
Piperonyl Butoxide		51-03-6	5.125
Pyrethrins		8003-34-7	0.512
Other components below reportable levels			2.05

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

General fire hazards

6. Accidental release measures

not breathe fumes.

Extremely flammable aerosol.

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to beat flame sparks, or other sources of ignition. All equipment used when

Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

ccupational exposure limits US. ACGIH Threshold Limit Components	Values Type	Value
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
	pational Health & Safety Code, Scheo	
Components	Туре	Value
Propane (CAS 74-98-6)	TWA	1000 ppm
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
		or Chemical Substances, Occupational Health and
Safety Regulation 296/97, as Components	amended) Type	Value
-	-	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
Canada. Manitoba OELs (Re Components	g. 217/2006, The Workplace Safety An Type	d Health Act) Value
Isobutane (CAS 75-28-5)	STEL TWA	1000 ppm
Pyrethrins (CAS 8003-34-7)		5 mg/m3
Canada. Ontario OELs. (Con Components	trol of Exposure to Biological or Cher Type	nical Agents) Value
Isobutane (CAS 75-28-5)	TWA	800 ppm
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
Canada. Quebec OELs. (Min Components	istry of Labor - Regulation Respecting Type	g the Quality of the Work Environment) Value
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
ological limit values	No biological exposure limits noted for	• • • • •
propriate engineering	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
ntrols	or other engineering controls to mainta	in airborne levels below recommended exposure limits. If
ntrols	or other engineering controls to mainta exposure limits have not been establist such as personal protective equipment	in airborne levels below recommended exposure limits. If ned, maintain airborne levels to an acceptable level. nt
ntrols	or other engineering controls to mainta exposure limits have not been establist such as personal protective equipment	in airborne levels below recommended exposure limits. If ned, maintain airborne levels to an acceptable level.
ntrols dividual protection measures,	or other engineering controls to mainta exposure limits have not been establist such as personal protective equipment	in airborne levels below recommended exposure limits. In ned, maintain airborne levels to an acceptable level. nt
dividual protection measures, Eye/face protection	or other engineering controls to mainta exposure limits have not been establish such as personal protective equipment Face shield is recommended. Wear sa	in airborne levels below recommended exposure limits. If ned, maintain airborne levels to an acceptable level. nt
dividual protection measures, Eye/face protection Skin protection	or other engineering controls to mainta exposure limits have not been establish such as personal protective equipment Face shield is recommended. Wear sa Wear appropriate chemical resistant gl	in airborne levels below recommended exposure limits. In ned, maintain airborne levels to an acceptable level. nt fety glasses with side shields (or goggles).
dividual protection measures, Eye/face protection Skin protection Hand protection	or other engineering controls to mainta exposure limits have not been establish such as personal protective equipment Face shield is recommended. Wear sat Wear appropriate chemical resistant glu supplier. Wear suitable protective clothing.	in airborne levels below recommended exposure limits. In ned, maintain airborne levels to an acceptable level. Int fety glasses with side shields (or goggles).
dividual protection measures, Eye/face protection Skin protection Hand protection Other	or other engineering controls to mainta exposure limits have not been establish such as personal protective equipment Face shield is recommended. Wear sat Wear appropriate chemical resistant glu supplier. Wear suitable protective clothing. If permissible levels are exceeded use	in airborne levels below recommended exposure limits. In ned, maintain airborne levels to an acceptable level. Int fety glasses with side shields (or goggles). oves. Suitable gloves can be recommended by the glove NIOSH mechanical filter / organic vapor cartridge or an

9. Physical and chemical properties

Appearance

Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.4 % estimated
Flammability limit - upper (%)	9.4 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	720.14 °F (382.3 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.705 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of
	NATE OF THE STREET AND A DESCRIPTION OF THE STREET

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the
physical, chemical and
toxicological characteristicsAspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Acute toxicity	May be fatal if swallowed and enters airways.		
Components	Species	Test Results	
Isobutane (CAS 75-28-5)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
Naphtha (petroleum), Hydrotreate	ed Heavy (CAS 64742-48-9)		
Acute			
Dermal			
LD50	Rabbit	> 1900 mg/kg, 24 Hours	
Inhalation			
LC50	Rat	> 5000 mg/m3, 4 Hours	
		> 4980 mg/m3	
		> 4980 mg/m3, 4 Hours	
		> 4.96 mg/l, 4 Hours	
Oral			
LD50	Rat	4820 mg/kg	
Piperonyl Butoxide (CAS 51-03-6)		
Acute			
Dermal			
LD50	-	> 2000 mg/kg	
Inhalation			
LC50	Rat	> 5.2 mg/l, 4 Hours	
Oral			
LD50	Rat	> 2000 mg/kg	
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
* Estimates for an dust mouth	he beend on additional common		
Skin corrosion/irritation	be based on additional compone Prolonged skin contact may		
Serious eye damage/eye	Direct contact with eyes may		
irritation	Direct contact with cycs may		
Respiratory or skin sensitizatio	on		
	OELs: Respiratory or skin se	nsitiser	
Pyrethrins (CAS 8003-34	· ·		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected	to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity			
Product name: B60401 KONK BLAS	STER - 350g	SDS CANADA	

	ACGIH Carcinogens		
	Pyrethrins (CAS 8003-34-7)		A4 Not classifiable as a human carcinogen.
Canada - Manitoba OELs: carcinoge		rcinogenicity	
	PYRETHRUM (CAS 8003-34-7)		Not classifiable as a human carcinogen.
IARC Monographs. Overall I		valuation of Carcinogenicity	
Piperonyl Butoxide (CAS 51-03-6)		51-03-6)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity This product is not expected		This product is not expected to	cause reproductive or developmental effects.
	Specific target organ toxicity - single exposure	Not classified.	
	Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard		May be fatal if swallowed and	enters airways.

12. Ecological information

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

	Species	Test Results	
AS 51-03-6)			
LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.0027 - 0.0043 mg/l, 96 hours	
-34-7)			
EC50	Water flea (Daphnia)	0.018 - 0.032 mg/l, 48 hours	
LC50	Brown trout (Salmo trutta)	0.0165 - 0.0229 mg/l, 96 hours	
	LC50 -34-7) EC50	AS 51-03-6) LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) -34-7) EC50 Water flea (Daphnia)	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n	Partition coefficient n-octanol / water (log Kow)		
Isobutane	2.76		
Piperonyl Butoxide	4.75		
Propane	2.36		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

•	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable

The second states (second	
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
· ·	Read safety instructions, SDS and emergency procedures before handling.
	tion requirements and may be shipped as a limited quantity.
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

IATA; IMDG; TDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations				
Controlled Drugs and Substances Act				
Not regulated.	Not regulated.			
Export Control List (CEPA 1	Export Control List (CEPA 1999, Schedule 3)			
Not listed.				
Greenhouse Gases				
Not listed.				
Precursor Control Regulation	ons			
Not regulated.				
International regulations				
Stockholm Convention				
Not applicable. Rotterdam Convention				
Not applicable. Kyoto protocol				
Not applicable.	Not applicable.			
Montreal Protocol				
Not applicable. Basel Convention				
Not applicable.				
International Inventories				
Country(s) or region	Inventory name	On inventory (yes/no)*		
Australia	Australian Inventory of Chemical Substances (AICS)	No		
Canada	Domestic Substances List (DSL)	Yes		
Canada	Non-Domestic Substances List (NDSL)	No		
China	Inventory of Existing Chemical Substances in China (IECSC)	No		
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No		
Europe	European List of Notified Chemical Substances (ELINCS)	No		
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No		
Korea	Existing Chemicals List (ECL)	No		
-	Existing Chemicals List (ECL) New Zealand Inventory	No No		
Korea	•			

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date	05-26-2017
Version #	01

	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names