# Material Safety Data Sheet

May be used to comply with

OSHA's Hazard Communication Standard,

29 CFR 1910.1200. Standard must be consulted for specific requirements.

# **U.S. Department of Labor**

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

| IDENTITY (As Used on Label and List) Lexol Leather Conditioner | Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be |
|--|--|
|  | marked to indicate that.   |

#### **Section I**

| Manufacturer's Name<br>Summit Industries, Inc.                                      | Emergency Telephone Number (770) 590-0600       |
|---|---|
| Address (Number, Street, City, State, and ZIP Code)<br>839 Pickens Industrial Drive | Telephone Number for Information (770) 590-0600 |
| Marietta, GA 30062  | Date Prepared<br>November 27, 2007              |
|   | Signature of Preparer (optional)                |

## Section II - Hazard Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity;<br>Common Name(s)) | OSHA<br>PEL |  | Other Limits<br>Recommended | %(optional) |  |  |
|--|-------------|--|-----------------------------|-------------|--|--|
| Lexol Leather Conditioner does not contain any hazardous components. |             |  |                             |             |  |  |
|  |             |  |                             |             |  |  |

## **Section III - Physical/Chemical Characteristics**

| Boiling Point   | 212° F  | Specific Gravity (H <sub>2</sub> O = 1) | 1   |  |  |
|---|---------|---|-----|--|--|
| Vapor Pressure (mm Hg.)   | 35mm Hg | Melting Point                           | n/a |  |  |
| Vapor Density (AIR = 1)   | 1       | Evaporation Rate (Butyl Acetate = 1)    | 1   |  |  |
| Solubility in Water Mixes with water                                  |         |   |     |  |  |
| Appearance and Odor<br>Moderately thick beige liquid. Soap-like odor. |         |   |     |  |  |

### Section IV - Fire and Explosion Hazard Data

| Flash Point (Method Used)<br>None          | Flammable Limits<br>None   | LEL<br>None                              | UEL<br>None |  |
|--|----------------------------|--|-------------|--|
| Extinguishing Media<br>None                | Special Fire Fighting None | Special Fire Fighting Procedures<br>None |             |  |
| Unusual Fire and Explosion Hazards<br>None |                            |  |             |  |
|  |                            |  |             |  |

LEXOL MSDS 11.27.07 1 of 2

# Section V - Reactivity Data

| Stability                                     | Unstable       |   | Conditions to Avoid<br>Heat. Containers may rupture. |  |
|---|----------------|---|--|--|
|   | Stable         | X |  |  |
| Incompatibility (Materials to Avoid) None     |                |   |  |  |
| Hazardous Decomposition or Byproducts<br>None |                |   |  |  |
| Hazardous<br>Polymerization                   | May Occur      |   | Conditions to Avoid Heat. Containers may rupture.    |  |
|   | Will Not Occur | X |  |  |

#### Section VI - Health Hazard Data

| Route(s) of Entry:  | Inhalation?<br>N/A | Skin?<br>X – possible  | Ingestion?<br>X - possible |  |  |
|---|--------------------|------------------------|----------------------------|--|--|
| Health Hazards (Acute and Chronic) Lexol Leather Conditioner is non-toxic and should be used as directed.       |                    |                        |                            |  |  |
| Carcinogenicity:  | NTP?<br>No         | IARC Monographs?<br>No | OSHA Regulated?<br>No      |  |  |
| Signs and Symptoms of Exposure<br>None  |                    |                        |                            |  |  |
| Medical Conditions Generally Aggravated by Exposure<br>None   |                    |                        |                            |  |  |
| Emergency and First Aid Procedures If ingested, seek medical assistance or contact local poison control center. |                    |                        |                            |  |  |

#### **Section VII - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled
May be discharged to public sewage system.

Waste Disposal Method
No special requirements. Pour down sink or absorb and put into trash.

Precautions to Be taken in Handling and Storing
Avoid heat above 140° F which may weaken containers. Avoid pressure that would damage shipping case.

Other Precautions
None required

#### **Section VIII - Control Measures**

| Respiratory Pro<br>None required                     | otection (Specify Type) |  |   |  |
|--|-------------------------|--|---|--|
| Ventilation<br>Not needed                            | Mechanical (General)    |  | Special<br>None                                       |  |
|  |                         |  | Other<br>None   |  |
| Protective Gloves<br>Not needed                      |                         |  | Eye Protection<br>Not needed - flush eyes if exposed. |  |
| Other Protective Clothing or Equipment<br>Not needed |                         |  | Work/Hygienic Practices<br>Nothing special            |  |

LEXOL MSDS 11.27.07 2 of 2